




Nst American.



50 mm x 90 mm x 20 mm SKF 210-2Z Cojinetes de bolas profundas

Bearing No. 210-2Z

210-2Z Bearing 2D drawings and 3D CAD models

Size	50x90x20 mm
Bore Diameter	50 mm
Outer Diameter	90 mm
Width	20 mm
d	50 mm
D	90 mm
B	20 mm
C	20 mm
d1	62,5 mm
r1 min.	1,1 mm
r2 min.	1,1 mm
D2	81,7 mm
da min.	57 mm
da max	62,4 mm
Da max.	83 mm
ra max.	1 mm
Weight	0,5 Kg
Basic dynamic load rating (C)	39,1 kN
Basic static load rating (C0)	34,5 kN
Fatigue load limit (Pu)	1,46
Reference speed	13000 r/min
Limiting speed	8000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF



Nst American.

Minimum Buy Quantity	N/A
Weight / Kilogram	0.533
EAN	7316577292766
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	Yes
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	50MM Bore; 90MM Outside Diameter; 20MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; Yes Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	210 2Z
Weight / LBS	1.15
Outer Race Width	0.787 Inch 20 Millimeter
Bore	1.969 Inch 50 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
bore diameter:	50 mm
static load capacity:	34.5 kN



Nst American.

outside diameter:	90 mm
precision rating:	ABEC 3 (ISO Class 6)
overall width:	20 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
outer ring width:	20 mm
row type & fill slot:	Single Row Filling Slot
fillet radius:	1 mm
snap ring included:	Without Snap Ring
maximum rpm:	8000 RPM
internal clearance:	C0
series:	21
dynamic load capacity:	39.1 kN
thrust application warning:	This product can not be used in Thrust Applications
d_1	62.51 mm
D_2	81.61 mm
$r_{1,2}$ min.	1.1 mm
d_a min.	57 mm
d_a max.	62.4 mm
D_a max.	83 mm
r_a max.	1 mm
Basic dynamic load rating C	39.1 kN
Basic static load rating C_0	34.5 kN
Fatigue load limit P_u	1.46 kN
Calculation factor k_r	0.04
Mass bearing	0.5 kg